



HULL

- Color - Oyster gel coat hull with colored inset and waterline [standard color options]
- Structural lamination w/multiple layers of hand laminated fiberglass reinforced plastic using knitted fiberglass
- Stringers - Continuous full length foam cored hand laminated fiberglass structural stringers
- Boarding platform integrated in hull w/ telescopic swim ladder
- Hull Guards - UV-stabilized PVC-guards: anchor, hull and sheer, 316 SS inset on hull side guard
- Fasteners - All exterior fasteners 316 SS
- Bottom Paint - Ablative black antifouling INTERLUX MICRON CSC® (2 coats)
- Bilge Pumps - 2000 GPH, in three compartments w/auto/manual switches at helm
- Bonding System - common bonding zincs on transom plus rudder, shoe & thruster zincs

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work deck areas
- Deck - Raised walk-around side decks
- Drains - cockpit
- Anchor Roller Assembly - Polished SS
- Bow Bitt - 316 SS Samson post
- Storage - hinged lid top deck box in cockpit w/drain
- Storage - Locking deck hatch to lazarette w/sealing gasket and spring-assist lifts
- Hand Rails - Deck, 1-1/4" bow and stern
- Hand Rails - 1-1/4" 316 SS full length hand rails over pilot house doors and each side of salon roof
- Hand Grabs - 316 SS forward of pilot house doors
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder-coated: sixteen windows (five opening w/screens)
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft hatch-style entry
- Portlights - 8" round black plastic w/screens (3)
- Cleats - 10" cap rail mounted 316 SS mooring cleats (8)
- Deck Fittings - 316 SS 2" fuel fill, SS 1-1/2" water fills (2), SS 1-1/2" waste suction on swim step
- Pennant Staff - On bow rail
- Lazarette Vents - SS powder coated louvered vents

PROPULSION / ENGINE ROOM

- Engine - Single 270hp CUMMINS® QSD4.2 electronic
- Marine Reduction Gear - ZF® 63 @ 2.78:1
- Alternator - 110 amp (12V)
- Fuel Filter - RACOR® 500MA10 for main engine
- Exhaust - 5" horizontal water lift muffler, transom exit
- Propeller - 24" HUNG SHEN® 4 blade bronze LH, tuned to Class 1 ISO-484 pitch tolerances
- Propeller Shaft - 1.75" SS w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Potable Water Pump - JABSCO® SensorMax-17® constant pressure
- Sound Insulation - 1-1/2" w/barrier and silver mylar finish

PROPULSION / ENGINE ROOM

- Lights - engine room (2)
- Outlet - 110VAC GFCI

HEATING

- Engine Heating System - w/three outlets

GALLEY

- Cook Top - two-burner alcohol/electric
- Microwave Oven - under counter, stainless steel finish
- Refrigerator , under counter - NOVA KOOL® R4500 AC/DC 4.3 cuft, teak faced
- Countertop - plastic laminate w/teak sea rail
- Sink - deep single basin polished SS w/single lever spray extension faucet and soap dispenser
- Cabinets - Solid teak face frames w/ teak doors and drawer faces
- Storage - Teak corner cabinet above counter with smoke glass/teak door
- Drawers - ApplePly®, solid teak faces, full extension ball bearing tracks & sea locks
- Outlets - 110VAC GFCI protected (2)

COMPANIONWAY

- Lights- stair, LED
- Gauges for black and potable water
- Hanging locker

SALON

- Storage Locker - w/laminate top
- Table - Teak mounted to fixed base
- Stereo Wiring - Prewired for two speaker locations from pilothouse
- Settee - Converts to double bed w/storage under [two teak drop down doors]
- Valances - Upholstered
- Lights - Disc style 12VDC Halogen Pewter bezel
- Lights - LED stair night lighting to illuminate treads
- Outlets - 110VAC (2)

PILOT HOUSE

- Helm seat - adjustable slider w/foot rest
- Overhead Instrument Console - full width, teak, w/12VDC terminal
- Engine Control - electronic single lever throttle/shift
- Fuel gauge - analog
- Engine Instrumentation - analog style w/LCD tachometer
- Bow Thruster Control - joystick
- Compass - RITCHIE® HF-743 flush mount
- Windshield wipers - pantograph style, adjustable speed, self park with washer systems (3)
- Fans - 12VDC (2)
- Stereo Wiring - prewired from overhead console to two stereo speaker locations aft
- Outlet - 110VAC
- Power Ports - 12VDC (2)

FORWARD CABIN (FOC'SLE)

- Full width island berth w/four drawers under, upholstered foam mattress
- Chain locker forward with access hatch



FORWARD CABIN (FOC'SLE)

- Hanging locker w/teak door
- Lights - 12VDC over berth (4)
- Lights - reading 12VDC (4)
- Outlet - 110VAC duplex
- Hatch - 22" w/screen
- Hullside cabinet w/teak door
- Sliding teak entry door

HEAD COMPARTMENT

- Toilet - TECMA® EasyFit [household size]
- Sink - oval stainless steel w/faucet
- Countertop - CORIAN® "Savannah"
- Shower - w/seat, curtain & track, textured shower sole
- Cabinet - vanity w/sliding door
- Cabinet - medicine
- Mirror - over sink
- Fixtures - toilet paper holder, towel rings & bar
- Door - teak locking entry
- Sealed sole inlays
- Lights - 12VDC overhead dome (2)
- Outlet - 110VAC GFCI
- Exhaust fan w/switch

INTERIOR FINISH AND TRIM

- Upholstery - choice of colors [see option sheet/samples]
- Carpet - choice of colors [see option sheet/samples]
- Cabinet Tops - Plastic laminate w/teak sea rail trim
- Valances, upholstered - salon
- Teak interior passageway doors and trim
- Overhead and bulkhead covering - vinyl w/foam backing
- Walls - teak wainscot paneling

LAZARETTE

- Fuel Tank
- Steering gear
- Completely gel coated and ventilated
- Storage space

STEERING SYSTEM

- Steering System - hydraulic
- Rudder and Shoe - SS w/ sacrificial zincs
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel - Teak
- Valves for autopilot hydraulic pump connection
- Bow Thruster - LEWMAR® 185TT 3.0kW 12V 4.0hp @ 128 lb thrust

12V DC ELECTRICAL SYSTEM

- Battery Charger - 40 amp 3-stage
- Batteries, Start/Thruster - 12V Group-31 (2) w/boxes
- Batteries, House - 6V deep cycle golf-cart type (2) w/boxes 220 amp hours
- Breaker Panel 12VDC - 36-position w/LED lights
- Master house bank circuit breaker switched at DC Panel
- Battery parallel switch
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Shore power connection - 30 amp, w/50' cord (1)
- Breaker panel - 110VAC w/LED lights

SAFETY & MOORING PACKAGE

- Fire Extinguishers - Class 5-B:C, shipped loose (2)
- High bilge water alarm - Sensor mounted in engine room w/ audible alarm at helm
- Exhaust overheat alarm - Temperature sensor on main engine wet elbow
- Carbon Monoxide detectors in each cabin & central seating area
- Smoke Detector in each cabin & in central seating area
- Radar reflector
- Horn - Dual electric
- Light - Anchor USCG approved
- Lights - Navigation USCG approved
- Mooring Lines - 5/8" x 25' (4)
- Fenders - G-5 and lines (4)
- NMMA Certification
- Canadian Declaration of Conformity

TANKAGE

- Fuel tank - 205-gallon
- Potable Water Tank - 100-gallon in two tanks w/crossover
- Gray Water Tank - 26-gallon with automatic 12V DC pump
- Black Water Tank - 30-gallon in keel, w/deck suction
- Tank Monitoring - Fuel, electric gauge at helm, and sight tube on tank
- Tank Monitoring - Potable water, electric gauge
- Tank Monitoring - Black water, in companion way
- Heater, Water - 6-gallon electric/engine heat

DIMENSIONS

- Length Overall - 34' 11" / 10.64m (rigged)
- Beam - 11' 1" / 3.38m
- Draft - 3' 11" / 1.19m
- Freeboard - Amidships, at pilothouse door 3' 9" / 1.14m
- Freeboard - at cockpit 2' 11" / 88.90cm
- Height from - Waterline-top to stack top 10' 0" / 3.05m
- Displacement Weight - 15,700 lbs / 7,136kg
- Headroom - Pilot House 6' 7" / 2.01m
- Headroom - Forward Cabin 6' 3" / 1.90m
- Headroom - Salon 6' 6" / 1.98m

COMMISSIONING PACKAGE

- Engine Manual
- Owners Manual - w/Schematics
- Reduction Gear Manual
- Tug Operators Manual
- Fuel filter element for primary RACOR® filters
- Matched gel coat touch-up kit
- Wax Paste - Ultra Performance® 3M9030
- Assortment of screws & snap caps
- Multi-Bit Screwdriver & SS Deck Fitting Key
- Clear silicone
- Shaft Seal O-Ring Kit
- Container boxes w/Lids - (2)