

HULL

- Color - White gel coat hull w/colored inset & waterline
- Structural lamination multi-directional knitted fiberglass w/vinyl ester skin coat
- Stringers – Fiberglass encapsulated full length composite stringers
- Boarding platform with stainless steel through bolted brackets and under mounted telescopic swim ladder
- Hull Guards - UV-stabilized black PVC-guards: anchor, and sheer-guard w/316 Stainless Steel inset
- Fasteners - All exterior fasteners 316 Stainless Steel
- Bottom Paint – Ablative antifouling (2 coats/black)
- Bilge Pumps - 2000 GPH in 2 compartments & 500 gph forward with auto/manual switches at helm
- Bonding System -anodes on transom, rudder, and shoe

DECK

- Color – White gel coat
- Deck - Molded textured surface in walking & work areas
- Deck - Raised side decks
- Drains - cockpit
- Anchor Roller Assembly
- Windlass - 1000W controlled at helm and foot controls
- Bow Bitt - 316 stainless steel Samson post
- Storage - Deck hatch to lazarette w/sealing gasket
- Deck Rails - Deck, 1" bow and stern
- Deck Box - hinged w/LPG 20# tank
- Hand Rails - 1" 316 stainless steel full length hand rails over pilot house doors and each side of salon roof
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Powder- coated finish, sliding windows in salon and pilothouse
- Doors - DIAMOND SEA GLAZE® Powder-coated: two sliding pilot house entry and one aft hatch style entry door w/drop sliding window and screen
- Portlights - 8" round stainless steel w/screens (2)
- Cleats - 8" cap rail mounted 316 stainless steel mooring cleats (6) w/chocks (2)
- Deck Fittings, 316 stainless steel - 2" fuel fill, 1-1/2" water fill, 1-1/2" waste suction

- Pennant Staff receiver - in bow rail
- Lazarette vents, polished Stainless Steel

PROPULSION / ENGINE ROOM

- Engine – Single Yanmar 110hp @ 3200 rpm diesel
- Alternator – 125 amp (12v)
- Fuel Filter - Primary 10 micron element secondary two micron element on the engine
- Exhaust - 3" horizontal water lift muffler, transom exit
- Propeller – Left Handed Rotation
- Propeller Shaft - 1.50" stainless steel w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Potable Water Pump – 12V Variable pressure
- Lights - engine room (2) LED
- Sound Insulation – Hush kit, 1" barrier silver Mylar
- Outlet – 110VAC GFCI

HEATING

- Heating System - Hydronic heat off engine with three outlets

GALLEY

- Cooktop - 2-burner propane
- Refrigerator, Nova Kool® R2600 12VDC under counter - [2.4cf / 68L] w/ black face
- Countertop – Laminate w/sea rail
- Sink - stainless steel, single bowl w/faucet
- Cabinets – Sapele faced
- Storage Locker
- Drawers - full extension ball bearing tracks & sea locks w/sapele faces
- Lights - Overhead, 12VDC LED (2)

COMPANIONWAY

- Lighted Storage locker 110VAC outlet, 12VDC/USB

SALON

- Dinette, Convertible to full berth w/ removable storage bins underneath, laminated table & sapele sea rail
- Outlets – 110VAC, 12VDC/ USB
- Lights - Overhead, 12VDC LED (2)
- Fusion Stereo with (2) speakers

PILOT HOUSE

- Helm seats - fixed w/foot rest
- Overhead Instrument Console
- Engine Control – Electronic single lever shift/ throttle
- Engine Monitoring – Keyless “C” display panel: water temp, oil pressure, voltmeter & tachometer
- Bow Thruster Control – joystick
- Compass - binnacle
- Windshield wipers - pantograph style, on/off (3)
- Fan - 12VDC
- Power Port - 12VDC/ USB
- Hatch - 20" w/ screen
- Stereo Speakers (2)

FORWARD CABIN (FOC'SLE)

- Offset full berth – upholstered foam mattress w/storage under
- Chain locker forward with access hatch
- Lights - Reading, 12VDC LED (2)
- Hatch - 20" with screen

HEAD COMPARTMENT

- Toilet – Jabsco electric sea water
- Molded one-piece head unit w/fiberglass sink and faucet/shower wand
- Shower - curtain & track, textured shower sole
- Mirror - On door
- Fixtures - towel ring, toilet paper holder & robe hook
- Door - Sapele entry with latch
- Lights - Overhead, LED
- Outlet - 110VAC GFCI

INTERIOR FINISH AND TRIM

- Upholstery – Choice of materials & colors (TBD)
- Carpet – Color (TBD)
- Cabinet Tops – Laminate tops with sea rail trim
- Sapele trim & doors
- Overhead and bulkhead covering – Foam back vinyl
- Walls – Foam back vinyl

LAZARETTE

- Gel coated and ventilated
- Steering gear
- Storage space

STEERING SYSTEM

- Steering System - manual hydraulic
- Rudder and Shoe – stainless steel w/sacrificial anode
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel – Stainless Steel
- Valves and fittings for autopilot hydraulic pump connection
- Bow Thruster - SIDE-POWER® SE40/125S 88lbs/40kg of Thrust

12V DC ELECTRICAL SYSTEM

- Battery, Start - 12V AGM Group-31 w/box, 950 CCA @ 32 degrees
- Batteries, House - 6V AGM deep cycle golf-cart type (2) w/boxes, 220 amp hours
- Breaker Panel 12VDC - BLUE SEAS w/LED lights
- Battery selector - BLUE SEAS® rotary switch
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Shore power connection - SMARTPLUG® 30A, with 50' cord, starboard
- Breaker panel - BLUE SEAS® 110VAC with LED lights ELCI main circuit breaker w/digital multi-meter
- Battery Charger – 12V Charger, 50 amp, 3 output

SAFETY PACKAGE

- Fire Extinguishers, (1) 5 LB and (2) 2 LB
- High bilge water alarm
- Smoke & CO2 detector in Fwd cabin & central seating area
- Radar reflector - located in stack
- Horn - Single Electric
- Light - Anchor, LED, USCG approved
- Lights - Navigation, LED, USCG approved
- NMMA Certification to ABYC Standards
- Canadian Declaration of Conformity

2021 Model Year Standard Equipment NordicTugs.com

TANKAGE

- Potable Water Polyethylene – 40 gallon in two tanks w/crossover line
- Fuel Tank – 100 gallon with sight tube
- Gray Water Sump for shower 800GPH
- Black Water – 20 gallon in keel, w/ deck pump out
- Tank Monitoring – Fuel analog at helm
- Tank Monitoring - Black water alarm light "full" at head
- Heater, Water - 6-gallon electric/engine heat

DIMENSIONS

- Length Overall - 28' 9" / 8.76m (w/swim platform & bow roller)
- Waterline length – 26' 4"
- Beam - 9' 6" / 2.89m
- Draft - 3' 3" / 0.99m
- Displacement Weight - 8,500 lbs / 3,859kg
- Height above waterline – 8' 7" to stack
- Headroom - Forward Cabin 6' 0" / 1.83m
- Headroom - Pilot House 6' 2" / 1.88m
- Headroom - Salon 6' 4" / 1.93m

OWNER'S PACKAGE

- Engine & Reduction Gear manuals
- Component owner's manuals
- Nordic Tug Operators Manual
- 10-micron fuel filter element for main engine RACOR®
- Matched gel coat touch-up kit
- Multi-Bit Screwdriver & Stainless Steel Deck Fitting Key
- Fenders & docking lines
- Shaft Seal Collar O-Ring Kit
- Container box w/ lid

Nordic Tugs Inc. reserves the right to change specifications and prices at any time.

2021 Specifications issued December 2019

Nordic Tugs, Inc.
11367 Higgins Airport Way
Burlington, WA 98233
(360) 757-8847